



**Volume 10 , March Issue 2021**

**INTERNATIONAL JOURNAL FOR  
INNOVATIVE ENGINEERING AND  
MANAGEMENT RESEARCH**

**IMPACT FACTOR 7,812**

WEBSITE: [WWW.IJEMR.ORG](http://WWW.IJEMR.ORG)

12.	ANALYTICAL INVESTIGATION OF RAIL WHEEL ASSEMBLY BY USING COMPOSITE MATERIALS  <b>THULASI SAI MAHESH KUMAR, ANAGANI SATEESH KUMAR</b>	84-93
13.	A FUZZY CONTROLLER BASED MULTI-INPUT HIGH STEP-UP CONVERTER FOR RENEWABLE ENERGY-DRIVE SYSTEMS  <b>K Swetha, R VASANTHI</b>	94-103
14.	Power Quality Improvement by using Active Power Filters in EV Charging Stations  <b>PANTAGANI JAYAPRAKSAH, A.ARUN KUMAR</b>	104-110
15.	Spectrum Efficient MIMO-FBMC System using Filter Bank Multicarrier System  <b>SHAIK JASMIN, SK.FARMANULLA</b>	111-121
16.	OFDM/OQAM PREAMBLE-BASED LMMSE CHANNEL ESTIMATION TECHNIQUE  <b>T.MADHAVA, B.SIVA NAGESWARA RAO</b>	122-127
17.	Digital Hybrid Video Dual Watermarking By Using SVD/DWT Technique  <b>M.SUNNY, SK.MUNWAR ALI</b>	128-133
18.	Comparative characteristics of the anthropometric parameters of the craniofacial region in children with adenoids  <b>N. P. Alimova, Sh. J. Tessaev</b>	134-137
19.	PLACE OF PHILOSOPHY OF LAW IN SOCIETY AND IN THE SYSTEM OF SCIENCES  <b>Madumarov Talantbek Tolibjonovich, Soliboev Umidbek</b>	138-139
20.	GREAT HISTORY  <b>M. Ganieva</b>	140-143
21.	MOUNTED MOLE-LEVELER  <b>A.Tukhtakuziyev, A.N.Murtazoev</b>	144-145
22.	Detection of anthropometric changes in children from birth to 3 years of age with congenital heart defects.  <b>S. Y. Saidova</b>	146-149
23.	TRIPLE OSTEOTOMY OF THE PELVIS IN TREATMENT OF HIPJOINT DYSPLASIA IN CHILDREN  <b>Ibragimov Sadulla Yusupovich, Eranov Nurali Fayziyevich, Eranov Sherzod Nuraliyevich</b>	150-152
24.	COMPARATIVE CHARACTERISTIC OF MORPHOMETRIC PARAMETERS IN RIGHT AND LEFT OF THE II PERIOD OF CHILDHOOD  <b>Rustamova N.B.</b>	153-155
25.	Ways and means of using eSIM technology in mobile networks for the use of IoT technologies in the security of robotic systems  <b>Zarif Zafarovich Kodirov, Sunatullo Nasriddin ugli Hojiev Asror Omon ugli Nasimov</b>	156-160
26.	DESIGN A HIGH-SPEED AND AREA-EFFICIENT VLSI ARCHITECTURE OF RCA USING 9T FULL ADDER  <b>MEDA SRI MAHA LAKSHMI, J ALLA BAGASH</b>	161-162



# International Journal for Innovative Engineering and Management Research

A Peer Reviewed Open Access International Journal

www.ijemr.org

**COPY RIGHT**



**ELSEVIER**  
**SSRN**

**2021 IJEMR.** Personal use of this material is permitted. Permission from IJEMR must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. No Reprint should be done to this paper, all copy right is authenticated to Paper Authors

IJEMR Transactions, online available on 5th March 2021. Link :  
<https://ijemr.org/index.php/downloads/Volume-10/ISSUE-3>

**DOI: 10.48047/IJEMR/V10/I03/21**

Title: **MOUNTED MOLE-LEVELER**

Volume 10, Issue 03, Pages: 144-145.

Paper Authors

**A.Tukhtakuziyev, A.N.Murtazoev**



USE THIS BARCODE TO ACCESS YOUR ONLINE PAPER

To Secure Your Paper As Per **UGC Guidelines** We Are Providing A Electronic Bar Code

## MOUNTED MOLE-LEVELER

A.Tukhtakuziyev, A.N.Murtazoev

**Abstract.** The article provides information on the device and the principle of operation, as well as the test results on the mount mole-leveler. It is established that when using a mounted mole-leveler, labor productivity increases by 1.45-1.54 times, labor expenses and other expenses are reduced by 34-37%.

**Keywords.** device, mole-leveler, labor expenses, labor productivity, drag-bar.

### I. Introduction.

In order to get rich harvest from agricultural plants it is important to process the soil before sowing. Because, if the soil is not processed before sowing, it will be impossible to sow the seeds of agricultural plants as qualitatively as required since the sown seeds do not bud totally and the expected harvest is not taken from each hectare. It will result in the decrease of the plant fertility.

It is known that, the main task in preparing the land for sowing consists of flattening the surface of fields, condensing it as required, grinding large clots of soil and forming the layer of delicate soil layer [1]. Nowadays, MB-6.0, MB-6.5 and other mole levelers present in farms are widely used for this purpose [2,3]. But they require energy-material as they are trailers, inconvenient to use, possess low maneuverability and labor productivity. They require a large square to turn (and for this a lot of time is required for making a back flip) and cleaning the spaces from plant remnants is accomplished with hand force. It requires a lot of time and results in disuse of the aggregate for a long time and decrease of labor productivity. Moreover, transferring the present mole leveler demands additional labor and means of transports.

Besides this, it is important to regard that, mole levelers are not manufactured so that to use them by connecting to high powered tractors widely used in our Republic at present.

Thus, working out "Magnum", MX-240, MX-255, AXION 810, ARION 640 C15, T7060 mounted mole levelers used by connecting to tractors is considered to be an important problem to be solved.

**Literature review.** Mount mole levelers are mainly used in territories which are engaged in agriculture including Middle Asia, Afghanistan, Pakistan, Azerbaijani and other countries of Near East. In territories engaged in irrigated farming including Russia, European countries and America levelers and rod rollers of different shape are used instead. Therefore, research works on manufacturing and developing the mount mole levelers and investigating their technological working processes and parameters were carried out by such scientists as d.t.s., professor-M.A.Akhmedjanov; candidates of technical sciences – V.N.Sokolov, A.Egamov and M.P. Kalimbetov [4-7]. On the basis of their investigations, such mount mole levelers as MB-6.0, MB-6.5, HO-2,1.000 were worked out. But they have the above mentioned defects. So, resulting from this, mount small-leveler was designed for the above mentioned tractors and its tests were experimented.

**Experimental method.** Tests of the experimental copies of a mount mole leveler was compared to present mole levelers by O'zDSt 3412.2019 "Experimenting the agricultural technique; Machines and devices for surface processing of the soil; Programs and methods of experiment" [8]. Here both the mole levelers were aggregated with a T7060 tractor.

**Gained results.** Mount mole leveler consists of a frame, device of hanging installed in it, a leveler and a condensing parts. It is used by connecting to the tractors of 3-4 class. During the working process, the leveling part of the mounted mole leveler flattens the uneven surfaces of the field and the condensing part condenses the soil as required. The pressure of the designed mounted mole leveler corrects the lower and upper drag bars by changing the state of connection of a tractor. If the pressure is not enough, drag bars are installed in upper holes of the hanging device of a mounted mole leveler and when the pressure is more than necessary in the lower holes of it.

By the results gained from tests it is known that in one passage a mount mole leveler processes the field surface enough as required and its usage increases the labor productivity 1.42- 1.54 times and reduces the labor and other expenses to 34-37%.

**Conclusion and recommendations.** In preparing the lands for sowing, using mount mole levelers increases the labor productivity 1.42- 1.54 times and reduces the labor and other expenses to 34-37%.

## REFERENCES

1. Sokolov F.A. Agronomic basis of complex mechanization of cotton growing.-Tashkent:Science, 1977.-p.224.
2. Model technological maps on growing agricultural plants and germinating products. For 2011-2015 (part 1). Min.Agr.Water Res. of the RU- Tashkent: "HILOL MEDIA", 2011.-P.43.
3. Repairing and effective using the cotton and grain gathering machines.-Tashkent: Science, 2012.-p.192.
4. Ahmedjanov M.A. Planning of irrigated lands.-Tashkent, 1991.-p.112.
5. Sokolov V.N. Investigation of device parameters for condensation of the land before sowing and leveling the soil in cotton growing: Dissertation of the candidate of tech. sciences.- Yangiyul, 1974.-p.150.
6. Egamov A.T. Base of the parameters of mole-leveler with regulated pressure on the soil: Dissertation of the candidate of tech. sciences. -Yangiyul, 1988.- p.151.
7. Kalimbetov M.P. Developing the technological process of the work and parameters of a mole-leveler. Dissertation of the candidate of tech. sciences. - Yangiyul, 2007.- p.130.
8. UzSS 3412.2019 "Application of agricultural techniques. Machines and devices for surface processing of the soil. Programs and methods of experiment". Tashkent, 2019.-p.54.