Bulletin news in New Science Society International Scientific Journal Vol. 1 Issue 6

Impact factor: 8.5 (Researchbib)

2024

BIOLOGICAL WAYS OF USING WASTE WATER

Bulletin sews in New Science Society second year

Bo'riyev Sulaymon Bo'riyevich-professor, Yuldoshov Laziz Tolibovich-docent. Umarov Otabek Rafoilovich - docent Bukhara State University, Qahhorov Nizom Qahhor o'g'li - Director of the Bukhara Scientific Experimental Station

Annotation: the article provides information on the growth, development, reproduction and degree of purification of wastewater from organo-mineral substances of the high water plant pistia (Pistia stratiotes L) oil refining plant wastewater.

Key words: high water growth, an increase in the runway (runway stratiotes L), biomass, oil plant, wastewater, pollution, dissolved oxygen in water, organic and mineral substances.

At present, the water problem in the world is considered an urgent problem. This is also the amount of water needed for them as a result of the increase in production and industrial enterprises. In the technological processes of enterprises, various products are developed, and a certain part of them fall into the waters, which leads to water pollution. As a result of the excretion of organic substances (petroleum products, dye substances, proteins, carbohydrates, etc.) in the water, leaky waters are formed in connection with the oxidation of the oxygen contained in the water, their consumption.

Flowing waters are divided into the following types:

One of them. From the communal economy (household) - kitchens, washing machines, and running water coming out of the baths

Two. From the sphere of production - wastewater contaminated with various substances, which are used in the production process.

Bulletin news in New Science Society International Scientific Journal 2024 Vol 1 Issue 6 Impact factor: 8.5 (Researchbib)

The three. On the account of atmospheric precipitation, The formed sizot waters-rain and snowy population punk, or flowing waters formed as a result of the washing of the territory of the enterprise.

The methods of cleaning the wastewater have been established.

One of them. Mechanical method (grinding, deposition, filtration, centrifugation), etc.G2.Physico-chemical method (adsorption, coagulation, flocculation, ion exchange, extraction)

The three. Chemical (reagent) method (neutralization, oxidation. reduction)

The four. Biochemical method (aerobic, anaerobic conditions)

The five. Thermal methods (flame cleaning in the presence of high temperatures)

The six. Biological method (with the help of plants)

The most useful among these methods is the biological method. Currently, in the world experience, specialized in the treatment of various wastewater treatment systems, which include purification methods, has been created. [1] industrial and other manufacturing enterprises are obliged to throw sewage pipes only after primary cleaning of wastewater contaminated with toxic chemicals. But some businesses are also releasing direct leaking water without cleaning or after a leaky gutter. This leads to disruption of the environment and ecology.

When cleaning by biological method, we clean water using several water plants. Of these, ryaska, azolla, pistia, plants are used. From high water plants, growers (ryaska, azolla, pistia, etc.) on the surface of the water are used in various branches of the national economy. The above plants are rich in physiologically active substances. To reproduce them, a large amount of mineral nutrients is required. Plants that are rich in carbohydrates, proteins, vitamins and other substances are being sown in wastewater from cities and production enterprises as well as agriculture in order to obtain and cheapen a large amount of biomass, and their level of purification of wastewater from various impurities is being studied.

Bulletin news in New Science Society International Scientific Journal 2024 Vol. 1 Issue 6 Impact factor: 8.5 (Researchbib)

Today, a lot of work is being done at Bukhara State University on biological purification. In the experiments of our scientists used the wastewater of the oil refinery.

The wastewater of the oil refinery contains various poisonous substances-naphthenic acid, mercanines, nitrogen and sulfur compounds, phenols, hydrogen sulphide, arsenic and others [2]. If the wastewater with such a composition is thrown into nature, it is dangerous for human life, including plants, animals, soils. Biological methods of purification of Okawa water, which preserve petroleum products, have been created [3].

Two variants of experiments were carried out in laboratory conditions by bringing out wastewater from the karavulbazar oil refinery into 20-liter circulating and square-shaped Aquariums. The physico-chemical composition of The brought wastewater was determined. Petroleum products containing wastewater contain 190 mg/l, the amount of oxygen dissolved in water is absent. Because oxygen is spent on oxidation of organic substances in water. Biochemical expenditure of oxygen (KBS5)-255,5 mg02/l; the degree of oxidation was 150,5 mg02/l, the amount of ammonia was 5,5 mg/l, nitrites-0,02 mg/l, nitrates-4,0 mg/l, sulfates-137 mg/l, chlorides-118 mg/l.

The amount of petroleum products in the water decreased to 13,7 mg/l in connection with the decomposition under the influence of bacteria and the conversion into mineral substances.

Chemical composition of oil slurry plant wastewater

Table-1

| Pointers | Composition of wastewater | Composition of wastewater at the end of the experiment | Biomass of the plant g/m ² | |
|---|---------------------------|--|---------------------------------------|--------|
| | | | Beginning | Ending |
| Temperature | 25,0 | 26,5 | 300 | 686 |
| рН- | 6,5 | 7,5 | | |
| Color | Magenta | White | | |
| Smell | 5,0 | 1,0 | | |
| Ingredients мг/л | 142 | 44,4 | | |
| Oxygen, мг/л | йўқ | 4,8 | | |
| КБС ₅ - мг 0 ₂ /л | 255,5 | 88,3 | | |
| Oxidation - $M\Gamma O_2/\Pi$ | 150,5 | 34,2 | | |
| Ammonium, мг/л | 5,5 | no | | |
| Nitritium, мг/л | 0,02 | no | | |
| Nitrogenium,мг/л | 4,0 | no | | |
| Sulphates, мг/л | 137 | 112,5 | | |

Bulletin news in New Science Society International Scientific Journal Vol. 1 Issue 6 Impact factor 85 (Researchhib.)

| TOUT I ISSUE O | | in pact ractor. Go (i tescai crisis) | | |
|-----------------|-----|--------------------------------------|--|--|
| Chlorides, мг/л | 118 | 94,2 | | |
| Petroleum | 190 | 13,7 | | |
| products, мг/л | | | | |

The experiments were continued and experiments were conducted, diluting the water with water in a ratio of 1:1 (50% aqueous-50% water of the water of the water of the water of the hydropower) due to the fact that the plant of the grows and is not active in the wastewater. A pistachio plant was planted in the amount of 300 g/m2 for aquariums, its development was observed. During the experiment, 3 times water temperature, pH-measured every day. 50% of water is diluted with water and pistachio plant is planted in it, the yield and the degree of water purification are given in Table 2.

The chemical composition of waters of the oil processing plant is determined by the high water content of the plant on the (diluted in 1: 1 ratio)

Table-2

2024

| Pointers | of wastewater | of wastewater at the end of the experiment | Beginning | Ending |
|-------------|---------------|--|-----------|--------|
| Temperature | 26,0 | 26,8 | 300 | 850 |
| pH- | 7,0 | 7,5 | | |
| Color | Yellowish | Without color | | |

Bulletin news in New Science Society International Scientific Journal 2024

Impact factor: 8.5 (Researchbib) Vol. 1 Issue 6 Smell 3,0 no Ingredients мг/л 64,3 43.5 Oxygen, мг/л 2,0 4,8 KBC_{5} - мг 0_{2} /л 147,5 31,8 Oxidation 159,0 27,2 $M\Gamma O_2/\Pi$ Ammonium, мг/л 2,0 no Nitritium, мг/л 0.02 no Nitrogenium,мг/л 3,8 no Sulphates, мг/л 101,5 94,5 Chlorides, мг/л 68,0 43,4 Petroleum 98.5 no products, мг/л

As can be seen from Table 2, when the wastewater of the oil refinery was diluted with water by 50%, the growth and development of the plant increased to a certain level and reached 850 Gramm on the water surface of 1 m2. Changes in the chemical composition of water were also observed. The amount of oxygen dissolved in water increased to 4,8 mg/l. The amount of organic substances contained in the water, that is, the biochemical consumption of oxygen was up to 31.8 mg02/l, the oxidation rate decreased to 27,2 mg02/l, ammonia in the environment, nitrites decreased and even disappeared from the environment. [5-6].

Conclusion. As a result of the conducted experiments, the oil refining enterprise actively developed a plant of (Pistia stratiotes L) in the flowing water and formed a biomass rich in a large amount of nutrients. In the active development of

Vol. 1 Issue 6 Impact factor: 8.5 (Researchbib)

the plant of (Pistia stratiotes L), it was found that it is possible to purify water from mineral substances by 90-95%, enriching the wastewater with oxygen dissolved in water. From the biomass formed, it was used as a feed in pig breeding.

REFERENCES

Фойдаланилган адабиётлар

- 1. Хўжжиев С.О., Оқава сувларнинг инновацион технологиялари. "Ўзбекистоннинг саноатлашган худудларида барқарор тараққиёт масалалари" Навоий-2019
 - . Львович А.И. Защита вод от загрязнения. Ленинград, 1977, 166 стр.
- 3. Буриев С.Б., Рашидов Н., Хайитов Ё., Хужжиев С. Короулбозор нефтни кайта ишлаш заводининг окова сувини тозалашнинг биотехнологияси. «Замонавий микробиология ва биотехнология муаммолари» мавзусидаги Республика илмий конференция материаллари. Тошкент-2009 й, 16-17 бет.
- 4. Таубаев Т. Т., Буриев С. Биологическая очистка сточных вод. Ташкент. 1980 г.
- 5. Лурье Ю.Ю. Аналитическая химия промышленных сточных вод. М. 1984 г
- 6.Строганов Н.С., Бузинова Н.С. Практическое руководство по гидрохимии. М.1980 г